

LIGATURE RESISTANT SHOWER HEAD

#SH340

Behavioral Safety's patented SH340 Ligature Resistant Shower Head features a unique pivoting head, directing the water stream up or down to allow full coverage for patients of different heights. This feature also works well for handicap patients. Zero side to side movement enables cleanliness to be maintained in the bathroom environment while also deterring any attempt by the patient to flood the bathroom. This polished chrome-plated, solid brass unit is wall mounted. The shower head itself has a 2-inch spray face with 42 spray channels.

An integral water conservation pressure compensating auto-flow device, reduces flow to 1.75 GPM/6.62 LPM maximum, which exceeds California title 20 Efficiency Standard. Improved water force is made possible by more efficient water channeling, providing a satisfying shower experience and reducing consumption.

Plumbing connection is made through a standard 1/2" NPTF back inlet.

Specifications

- Supply Inlet: 1/2" NPTF
- Flow Rate: 1.75 GPM/6.62LPM Maximum
- Flow Control: Variable
- Integral Pivot Feature
- Mounted from front of wall.
- Brass construction with polished chrome plated exterior.
- Pick-free joint caulk recommended.
- ASME A112.18.1/CSA B125.1, WaterSense, CEC, and DOE certified.
- Shipping weight 4 lbs.

Important

- Be sure to read instructions thoroughly before beginning installation.
- Do not over-tighten any connections or damage may occur.

Safety Tips

Cover your drain to prevent loss of parts. Be sure to wear eye protection and follow all tool manufacturer's safety recommendations.

